X-17401

UNITED STATES ATOMIC ENERGY COMMISSION

# MULTI-GROUP, MULTI-REFLECTOR PILE THEORY

By
H. L. Garabedian
A. S. Householder

DTIC QUALITY INSPECTED 2

February 12, 1947

Clinton Laboratories
Oak Ridge, Tennessee

Technical Information Service, Oak Ridge, Tennessee

19970423 100

Date Declassified: September 20, 1955.

MULTI-GROUP, MULTI-REFLECTOR PILE THEORY

Section VI

By

H. L. Garabedian
A. S. Householder

February 12, 1947

Work performed under Contract No. W-35-058-Eng-71

G. Young, Section Chief
CLINTON LABORATORIES
Oak Ridge, Tennessee

Multi-Group, Multi-Reflector Pile Theory

1. __Introduction.__ The differential equations involved in
the multi-group, multi-reflector pile theory studied in th's paper
are homogeneous partial differential equations of the second order.
Associated with the pile or any of the reflectors is a system of
as many equations as there are groups. Thus, if there are n groups
and ν reflectors there is a system of n second order equations in
each of the $\nu + 1$ regions, the solutions of the $\nu + 1$ systems
satisfying appropriate continuity conditions at the boundaries.

There are three types of piles considered: the infinite slab,
the infinite cylinder, and the sphere. Moreover, symmetrical
characteristics of the problems are such that the partial differential
equations reduce to ordinary differential equations. Although the
equations are linear, the coefficients are constant only in the case
of the slab pile; otherwise, they are functions of the independent
variable.

Ordinarily, the problem to be solved is to find the neutron
density at any point within the region bounded by the outermost
reflector and to find the critical size of the pile, after the
dimensions of the reflectors have been assigned. In all three cases
mentioned the general solution of the set within each region is
easily written down, even where the coefficients are variable.
Thereafter, a difficulty arises in that the location of the
boundaries is not assigned but is dependent upon the size of the

pile. Thus, a procedure for the solution of the problem is to solve the equations sequentially from the pile through all of the reflectors in terms of a fixed but unspecified critical size (radius or half-width) until the outer boundary is reached. Then, the outer boundary conditions together with requirements of symmetry within the pile provide sufficient specifications for the determination of critical pile size and the complete solution of the problem.

In a previous report, Mon P-202, the two-group theory for the case of multiple reflectors, without multiplication in the reflectors, and an infinite slab pile is discussed. In the determination of critical size it is found that the contribution of each reflector to the solution of the problem is independent of pile size. The equation which finally yields the critical size involves a single fourth order determinant, whose first two columns only involve the pile size, and whose last two columns are obtainable as a product of $\nu - 1$ fourth order matrices and one 4×2 matrix (four rows and two columns), all independent of pile size.

In this paper the problem is discussed from a more general point of view which includes the consideration of possible multiplication in the reflectors and three different pile shapes. First of all, the system of n second order differential equations is replaced by a system of $2n$ first order differential

equations. This procedure embraces all of the advantages of
the first study while further providing better general
perspective on the problem and simplifying somewhat certain
computational aspects of the problem. The simplicity first
achieved in the infinite slab case is preserved in the new
procedure, but does not persist in the spherical and
cylindrical cases for either method. However, in all cases
it is possible to reduce the order of the fundamental
determinant for the determination of critical pile size to
exactly the number of groups involved in the problem.

In § 2 a special example is provided for the case of two
groups and an arbitrary number of reflectors in an infinite
slab pile, with multiplication in the reflectors. In § 3 the
case of the infinite slab pile is treated with full generality.
General treatments of the spherical and cylindrical cases are
given in § 4 and § 5 respectively. Finally, in § 6, a study is
made of the limiting situation in the case of the infinite slab
pile and the spherical pile to provide an n - group theory with
a reflector of variable density.

2. The two-group, multi-reflector problem for the infinite
slab pile.

2.1. The differential equations and boundary conditions.
Let y, with an appropriate subscript to represent a particular
group, represent the flux of the neutrons of this group in any of

the $\nu + 1$ regions consisting of the pile and the reflectors. Let y_1 represent the flux of thermal neutrons and y_2 the flux of non-thermal neutrons. The equations in any region have the form

$$\lambda_1 \frac{d^2 y_1}{dx^2} - \lambda_1 K_1^2 y_1 + \lambda_2 K_2^2 y_2 = 0 \ ,$$

(2.1.1)

$$\lambda_2 \frac{d^2 y_2}{dx^2} - \lambda_2 K_2^2 y_2 + k \lambda_1 K_1 y_1 = 0 \ ,$$

where the constant k is zero in a reflector without multiplication.

The boundary conditions prescribe the continuity of y_i and $\lambda_i \frac{dy_i}{dx}$, for $i = 1, 2$, at the intermediate boundaries and the vanishing of y_i at the outer boundary.

2.2. Reduction to a system of first order differential equations. If in (2.1.1) the substitutions

$$y_3 = \lambda_1 y_1' \ .$$

$$y_4 = \lambda_2 y_2'$$

are made, the system of first order equations which follow is obtained:

$$y_1^0 = \lambda_1^{-1} \ y_3 \ .$$

(2.2.1)
$$y_2^0 = \lambda_2^{-1} \ y_4 \ .$$

$$y_3^0 = \lambda_1 \kappa_1^2 \ y_1 - \lambda_2 \kappa_2^2 \ y_2 \ .$$

$$y_4^0 = - k \lambda_1 \kappa_1^2 \ y_1 + \lambda_2 \kappa_2^2 \ y_2 \ .$$

Now, let the symbol y without a subscript denote the column vector of components y_1, y_2, y_3, y_4. Then, the equations (2.2.1) can be written in the matrix form

$$y^0 = My \ ,$$

where

$$M = \begin{pmatrix} 0 & 0 & \lambda_1^{-1} & 0 \\ 0 & 0 & 0 & \lambda_2^{-1} \\ \lambda_1 \kappa_1^2 & - \lambda_2 \kappa_2^2 & 0 & 0 \\ - k \lambda_1 \kappa_1^2 & \lambda_2 \kappa_2^2 & 0 & 0 \end{pmatrix} \, .$$

Solution of the problem for the case of no multiplication in the reflectors.

Solutions of the form $y_i = A_i e^{\cdots x}$, $i = 1$, 2, 3, 4, are now sought. Substitution in (2.2.1) yields the equations

$$A_1 \mu = \lambda_1^{-1} A_3 \quad .$$

$$A_2 \mu = \lambda_2^{-1} A_4 \quad .$$

$$A_3 \mu = \lambda_1 K_1^2 A_1 - \lambda_2 K_2^2 A_2 \quad .$$

$$A_4 \mu = - k \lambda_1 K_1^2 A_1 + \lambda_2 K_2^2 A_2 \quad .$$

which have a non-trivial solution in A_1, A_2, A_3, A_4 provided that

(2.3.1)
$$\begin{vmatrix} -\mu & 0 & \lambda_1^{-1} & 0 \\ 0 & -\mu & 0 & \lambda_2^{-1} \\ \lambda_1 K_1^2 & -\lambda_2 K_2^2 & -\mu & 0 \\ -k\lambda_1 K_1^2 & \lambda_2 K_2^2 & 0 & -\mu \end{vmatrix} = 0 \quad .$$

This is the characteristic equation of the system (2.2.1).

The equation (2.3.1) can be written in the form

$$\begin{vmatrix} 0 & 0 & \lambda_1^{-1} & 0 \\ 0 & 0 & 0 & \lambda_2^{-1} \\ \lambda_1(K_1^2 - \mu^2) & -\lambda_2 K_2^2 & -\mu & 0 \\ -k\lambda_1 K_1^2 & \lambda_2(K_2^2 - \mu^2) & 0 & -\mu \end{vmatrix} = 0 \quad .$$

and consequently

$$\begin{vmatrix} \mathcal{K}_1^2 - \mu^2 & -\mathcal{K}_2^2 \\ -k\,\mathcal{K}_1^2 & \mathcal{K}_2^2 - \mu^2 \end{vmatrix} = 0 \quad .$$

or

$$(2.3.2) \qquad (\mathcal{K}_1^2 - \mu^2)(\mathcal{K}_2^2 - \mu^2) - k\,\mathcal{K}_1^2\,\mathcal{K}_2^2 = 0 \; .$$

In the pile $k > 1$ and the equation (2.3.2) in μ^2 has one positive and one negative root. Thus, the four roots of (2.3.2) may be written in the form $\pm i\,\mu_1$, $\pm\mu_2$, where μ_1 and μ_2 are real and positive numbers. In this section it is assumed that $k = 0$ in the reflectors, and the corresponding roots of (2.3.2) are $\pm\mathcal{K}_1$, $\pm\mathcal{K}_2$. In either case there exists a set of four independent solutions of the system (2.2 1). Let each solution of any independent set of solutions be made a column of a 4×4 matrix Y. To illustrate, a matrix Y_α corresponding to the α - th region * of the pile is constructed. One uses a solution of the form $y_1 = A_1 e^{\mathcal{K}_1 x}$, taking $A_1 = 1$, in the equations (2.2.1) to get the first column in Y_α. In this case it is found that $A_3 = A_4 = 0$. The substitution $y_1 = A_1 e^{-\mathcal{K}_1 x}$ gives the second column, and so on. The final result for $\alpha > 0$ is

---

*Until further notice in this section a subscript shall henceforth designate a particular region instead of a particular group.

$X_\alpha(x) =$

$$\begin{pmatrix} e^{K_1 x} & e^{-K_1 x} & e^{K_2 x} & e^{-K_2 x} \\ 0 & 0 & \lambda_1 \lambda_2^{-1} K_2^{-2}(K_1^2 - K_2^2)e^{K_2 x} & \lambda_1 \lambda_2^{-1} K_2^{-2}(K_1^2 - K_2^2)e^{-K_2 x} \\ \lambda_1 K_1 e^{K_1 x} & -\lambda_1 K_1 e^{-K_1 x} & \lambda_1 K_2 e^{K_2 x} & -\lambda_1 K_2 e^{-K_2 x} \\ 0 & 0 & \lambda_1 K_2^{-1}(K_1^2 - K_2^2)e^{K_2 x} & -\lambda_1 K_2^{-1}(K_1^2 - K_2^2)e^{-K_2 x} \end{pmatrix}$$

which is a non-singular matrix. By taking appropriate linear
combinations of the columns of this matrix one may replace the
above matrix Y_α by a new one

$Y_\alpha(x) =$

$$\begin{pmatrix} \text{sh } K_1 x & \text{sh } K_2 x & \text{ch } K_1 x & \text{ch } K_2 x \\ 0 & s_1 \text{sh } K_2 x & 0 & s_1 \text{ch } K_2 x \\ \lambda_1 K_1 \text{ch } K_1 x & \lambda_1 K_2 \text{ch } K_2 x & \lambda_1 K_1 \text{sh } K_1 x & \lambda_1 K_2 \text{sh } K_2 x \\ 0 & \lambda_2 s_1 K_2 \text{ch } K_2 x & 0 & \lambda_2 s_1 K_2 \text{sh } K_2 x \end{pmatrix}$$

where

$$s_1 = \lambda_1 \lambda_2^{-1} K_2^{-2}(K_1^2 - K_2^2) \; .$$

For later reference the matrix Y_0, corresponding to the pile,

is computed to be

$Y_0 (x) =$

$$\begin{pmatrix} \cos \mu_1 x & \ch \mu_2 x & \sin \mu_1 x & \sh \mu_2 x \\ r_1 \cos \mu_1 x & r_2 \ch \mu_2 x & r_1 \sin \mu_1 x & r_2 \sh \mu_2 x \\ -\lambda_1 \mu_1 \sin \mu_1 x & \lambda_1 \mu_2 \sh \mu_2 x & \lambda_1 \mu_1 \cos \mu_1 x & \lambda_1 \mu_2 \ch \mu_2 x \\ -r_1 \lambda_2 \mu_1 \sin \mu_1 x & r_2 \lambda_2 \mu_2 \sh \mu_2 x & r_1 \lambda_2 \mu_1 \cos \mu_1 x & r_2 \lambda_2 \mu_2 \ch \mu_2 x \end{pmatrix}$$

where

$$r_1 = \lambda_1 \lambda_2^{-1} K_2^{-2} (K_1^2 + \mu_1^2) ,$$

$$r_2 = \lambda_1 \lambda_2^{-1} K_2^{-2} (K_1^2 - \mu_2^2) ,$$

One bears in mind that the parameters K and λ which occur here are

those characterizing the material of the pile and are distinct

from those occurring in the matrix Y_α written above.

In general, then, the matrix $Y(x)$ for each region is a

non-singular matrix of functions of x satisfying the matrix

equation

$$Y' = MY.$$

Since M is a constant matrix the related system of equations have

constant coefficients. It is then clear that if in the matrix

$Y(x)$, the independent variable x is everywhere replaced by $x - x_0$, the resulting matrix $Y(x - x_0)$ is also a matrix of independent solutions if x_0 designates any point within or on a boundary of the region (pile or reflector) over which the differential equations are defined. Indeed, the replacement of x by $x - x_0$ is merely a transformation of the independent variable which has no effect upon the form of the equations. Moreover, every solution of the equations is expressible in the form $y = Yc$, where c is a column vector of four elements.

One now takes the origin as the center of the pile and $x_{\alpha -1}$ and x_{α} as the bounds of the α - th region. Accordingly, the matrix Y_{α} may be taken as a function of $x - x_{\alpha -1}$, that is, of the distance from the inner boundary of the region to an arbitrary point of the region.

The conditions of continuity at the pile and reflector boundaries require that

$$y_{\alpha}(x_{\alpha} - x_{\alpha -1}) = y_{\alpha +1}(0) \ .$$

or, if $\qquad t_{\alpha} = x_{\alpha} - x_{\alpha -1} \ ,$

$$y_{\alpha}(t_{\alpha}) = y_{\alpha +1}(0) \ .$$

Notice that in the last equation neither x_{α} nor $x_{\alpha -1}$ appears, but only the thickness t_{α} of the α - th region.

Suppose now that a solution y_0 were given for the pile.

This could be expressed in the form

$$y_0 = Y_0 \, c_0$$

where Y_0 is the particular matrix of fundamental solutions which has been chosen within the region of the pile. Now, the solution $y_1 = Y_1 \, c_1$ in the first reflector must satisfy the relation

$$y_1(0) = y_0(a)$$

where $a = t_0$ is the half-thickness of the pile.
Hence,

$$Y_1(0)c_1 = Y_0(a)c_0 \quad .$$

and, since all of the Y_α 's have been chosen non-singular, one obtains

$$c_1 = Y_1^{-1}(0)Y_0(a)c_0 \quad .$$

Again, at the next boundary,

$$y_2(0) = y_1(t_1) \quad .$$

or

$$Y_2(0)c_2 = Y_1(t_1)c_1 \quad .$$

so that

$$c_2 = Y_2^{-1}(0)Y_1(t_1)c_1 \quad .$$

or

$$c_2 = Y_2^{-1}(0)Y_1(t_1)Y_1^{-1}(0)Y_0(a)c_0$$

If this procedure is continued one obtains

$$(2.3.4) \quad c_\alpha = Y_\alpha^{-1}(0)Y_{\alpha-1}(t_{\alpha-1})Y_{\alpha-1}^{-1}(0) \ldots Y_0(a)c_0 .$$

Thus, if the vector c_0 (or the solution y_0 within the pile) and the half-thickness $\underline{a}$ of the pile were known, the solution within all of the reflectors could be obtained.

The situation last considered does not generally arise, and both y_0 and $\underline{a}$ must be obtained from other conditions. The physical situation requires that the solution be symmetric within the pile. Accordingly, the last two components of the vector y_0 must vanish at the outer boundary; that is, the first two components of the vector y_ν must vanish at the outer boundary. To express these requirements in symbolic form let Y_0 and Y_ν be partitioned into 2 x 4 matrices:

$$Y_0 = \begin{pmatrix} Y_{o1} \\ Y_{o2} \end{pmatrix} . \qquad\qquad Y_\nu = \begin{pmatrix} Y_{\nu 1} \\ Y_{\nu 2} \end{pmatrix} .$$

and then require that

$$(2.3.5) \qquad\qquad Y_{o2}(0)c_0 = 0 .$$

$$(2.3.6) \qquad\qquad Y_{\nu 1}(t_\nu)c_\nu = 0 .$$

If the matrix Y_0 is written in the form (2.3.3) the requirement (2.3.5)

is met by making the last two components of the vector c_0 equal
to zero. The end result is the same if one drops out the last
two columns of Y_0 thus making it a 4×2 matrix composed of the
first two columns of (2.3.3), and it will be assumed that this
has been done in what follows.

Now, in (2.3.4), set $\alpha = \beta$ and multiply on the left by
$Y_{\nu 1}(t_\nu)$. Then it follows from (2.3.6) that

$$Y_{\nu 1}(t_\nu)Y_\nu^{-1}(0)Y_{\nu -1}(t_{\nu -1})Y_{\nu -1}^{-1}(0) \ldots Y_0(a)c_0 = 0 \quad .$$

The matrix $Y^{-1}(0)Y_{\nu -1}(t_{\nu -1})Y_{\nu -1}^{-1}(0) \ldots Y_0(a)$ is a 4×2 matrix
since $Y_0(a)$ is a 4×2 matrix, and $Y_{\nu 1}(t_\nu)$ is a 2×4 matrix.
Then the product is a 2×2 matrix. The equations are consistent
if and only if the determinant of the coefficients vanishes:

$$(2.3.7) \quad \left| Y_{\nu 1}(t_\nu)Y_\nu^{-1}(0)Y_{\nu -1}(t_{\nu -1})Y_{\nu -1}^{-1}(0) \ldots Y_0(a) \right| = 0 \quad ,$$

The determinant is of order two and the solution of the equation
gives the critical pile size $\underline{a}$.

The computation is simplified in a numerical problem if
$Y_\nu(x - x_{\nu -1})$ is replaced by $Y_\nu(x - x_\nu)$. This has the effect
of making the last two components of the vector c_ν equal to zero,
and condition (2.3.6) becomes

$$Y_{\nu 1}(0)c = 0 \quad .$$

Equation (2.3.7) is now written

$$\left| Y_{\nu_2}^{-1}(-t_\nu) Y_{\nu-1}(t_{\nu-1}) Y_{\nu-1}^{-1}(0), \dots, Y_0(s) \right| = 0 \ .$$

As a matter of record the following formulas are listed:

$$Y_\nu(0) = \begin{pmatrix} 0 & 0 & 1 & 1 \\[2mm] 0 & 0 & 0 & s_1 \\[2mm] \lambda_1 \kappa_1 & \lambda_1 \kappa_2 & 0 & 0 \\[2mm] 0 & \lambda_2 s_1 \kappa_2 & 0 & 0 \end{pmatrix}$$

$$Y_\nu^{-1}(0) = \begin{pmatrix} 0 & 0 & \lambda_1^{-1}\kappa_1^{-1} & -s_1^{-1}\lambda_2^{-1}\kappa_1^{-1} \\[2mm] 0 & 0 & 0 & s_1^{-1}\lambda_2^{-1}\kappa_2^{-1} \\[2mm] 1 & -s_1^{-1} & 0 & 0 \\[2mm] 0 & s_1^{-1} & 0 & 0 \end{pmatrix}$$

$$Y_\nu(t_\nu) Y_\nu^{-1}(0) =$$

$$\begin{pmatrix} \operatorname{ch}\kappa_1 t_\nu & \frac{1}{s_1}(\operatorname{ch}\kappa_2 t_\nu - \operatorname{ch}\kappa_1 t_\nu) & \operatorname{sh}\kappa_1 t_\nu & \frac{1}{s_1\lambda_2}\left(\frac{\operatorname{sh}\kappa_2 t_\nu}{\kappa_2} - \frac{\operatorname{sh}\kappa_1 t_\nu}{\kappa_1}\right) \\[3mm] 0 & \operatorname{ch}\kappa_2 t_\nu & 0 & \frac{1}{\lambda_2\kappa_2}\operatorname{sh}\kappa_2 t_\nu \\[3mm] \lambda_1\kappa_1\operatorname{sh}\kappa_1 t_\nu & \frac{\lambda_1}{s_1}(\kappa_2\operatorname{sh}\kappa_2 t_\nu - \kappa_1\operatorname{sh}\kappa_1 t_\nu) & \operatorname{ch}\kappa_1 t_\nu & \frac{\lambda_1}{s_1\lambda_2}(\operatorname{ch}\kappa_2 t_\nu - \operatorname{ch}\kappa_1 t_\nu) \\[3mm] 0 & \lambda_2\kappa_2\operatorname{sh}\kappa_2 t_\nu & 0 & \operatorname{ch}\kappa_2 t_\nu \end{pmatrix} .$$

The first two rows only occur in the determinant of (2.3.7).

It should be emphasized that in the preceding formulas the subscripts on the Y's and t's refer to a particular region (pile or reflector) and the subscripts elsewhere designate a particular group. When these formulas are used for actual computation a double subscript notation (ij) should be used, where i designates the region and j designates the group.

2.4. Further observations on the solution. It is possible that the computation in the problem of the preceding section can be simplified by making the matrix $Y_\nu(0)$ of initial values the identity matrix. It is clear that if $Y_\nu(x - x_{\nu-1})$ is any non-singular matrix of solutions then so also is the matrix

$$W_\alpha(x - x_{\alpha-1}) = Y_\alpha(x - x_{\alpha-1})Y_\alpha^{-1}(0)$$

and moreover

$$W_\nu(0) = I$$

Then, the fundamental equation (2.3.7) becomes

$$\left| W_{\nu 1}(t_\nu)W_{\nu-1}(t_{\nu-1}) \cdots W_{02}(a) \right| = 0$$

where $W_{\nu 1}(t_\nu)$ consists of the first two rows of $W_\nu(t_\nu)$ and $W_{02}(a)$ consists of the first two columns of $W_0(a)$.

In the preceding section the formula

$$(2.4.1) \qquad c_N = Y_N^{-1}(0)Y_{N-1}(t_{N-1})Y_{N-1}^{-1}(0) \cdots Y_0(a)c_0 = P c_0$$

was obtained without imposing any restriction on the matrix of

solutions Y_α beyond its non-singularity. It is now observed that (2.4.1) can be written in the equivalent form

$$c_0 = Y_0^{-1}(a)Y_1(0)Y_1^{-1}(t_1) \ldots Y_N(0)c_N \equiv P^{-1}c_N$$

Accompanying conditions required that

$$(0_2 \cdot I_2)Y_0(0)c_0 = 0 \quad ,$$

$$(I_2 \cdot 0_2)Y_N(t_N)c_N = 0 \quad ,$$

where 0_2 and I_2 are 2×2 zero - and identity - matrices, respectively. By the special choice of Y_0 whereby a partitioning of $Y_0(0)$ has the form

$$\begin{pmatrix} A & B \\ 0 & C \end{pmatrix} \cdot$$

the condition on the vector c_0 alone is equivalent to the requirement that the last two components of c_0 be zero. The subsequent elimination of the two vectors c_0 and c_N was found to yield a determinant of order two in the final equation of the problem. A similar special choice of Y_N is useful when the outer reflector is infinite in the x - direction. To this end one chooses the first two columns of Y_N to be a set of solutions of the differential equations which vanish at infinity. Hence, the last two components of c_N are both zero and there remains the

determinantal equation

$$(2.4.2) \quad \left| Y_{N2}^{-1}(0) Y_{N-1}(t_{N-1}) \ldots Y_{o1}(a) \right| = 0 \quad .$$

where $Y_{N2}^{-1}(0)$ is the lower half of the matrix $Y_N^{-1}(0)$ and $Y_{o1}(a)$ the left-hand half of the matrix $Y_o(a)$.

A procedure which simplifies the computation of $Y_{N2}^{-1}(0)$ in equation (2.4.2) has been suggested by B. Spinrad. A special choice of the last two columns in Y_N is made so that the task of computing $Y_N^{-1}(0)$ is made as simple as possible. One writes $Y_N(x)$ in the form

$$Y_N(x) =$$

$$\begin{pmatrix} e^{-K_1 x} & e^{-K_2 x} & \dfrac{\text{sh} K_1 x}{\lambda_1 K_1} & \dfrac{1}{\lambda_2 s_1 K_1 K_2}(K_1 \text{sh} K_2 x - K_2 \text{sh} K_1 x) \\[2ex] 0 & s_1 e^{-K_2 x} & 0 & \dfrac{\text{sh} K_2 x}{\lambda_2 K_2} \\[2ex] -\lambda_1 K_1 e^{-K_1 x} & -\lambda_1 K_2 e^{-K_2 x} & \text{ch} K_1 x & \dfrac{\lambda_1}{\lambda_2 s_1}(\text{ch} K_2 x - \text{ch} K_1 x) \\[2ex] 0 & -\lambda_2 s_1 K_2 e^{-K_2 x} & 0 & \text{ch} K_2 x \end{pmatrix} \quad ,$$

so that $Y_N(0)$ takes the form

$$\begin{pmatrix} A & 0 \\ B & I \end{pmatrix} \quad .$$

the inverse of which is readily computed. It is the lower half of this inverse which is used in (2.4.2).

In case the pile is not symmetric there is no requirement
of symmetry at the center. Instead, if O and N designate the
two outer reflectors, it is required that

$$(I_2, O_2)Y_0(0)c_0 = 0 .$$

$$(I_2, O_2)Y_N(t_N)c_N = 0 .$$

provided that both outer reflectors are finite. The special choice
of both Y_0 and Y_N results in $Y_0(0)$ and $Y_N(t_N)$ having the partitioned
form

$$\begin{pmatrix} 0 & B \\ A & C \end{pmatrix} .$$

This means that the first two columns of each vanish in their first
two components at the outer boundaries. In case either reflector
is infinite in the x - direction the requirements on $Y_0(0)$ or
$Y_N(t_N)$ are meaningless, but in this case the first two columns of
the Y matrix are chosen to vanish at infinity. In either case,
the last two components of c_0 and c_N are zero. Note that if the
zero - reflector is infinite, the origin must be moved to its inner
boundary. Now, if c_{o1} and c_{N1} denote the two-vectors of non-zero
components there results either of the equivalent sets of 2 x 2
equations of the form

$$Qc_{o1} = 0 , \quad Rc_{N1} = 0 .$$

from which one obtains either of the equivalent determinantal
equations

$$Q \; = \; 0 \; , \quad R \; = \; 0 \; ,$$

If it is assumed for the sake of simplicity that all of the reflectors are finite, note that it makes little difference which of the N regions is left with its thickness undetermined. The unknown thickness t_k is involved in only a single matrix of the product Q or R. This matrix is multiplied on the left by a constant matrix of dimensions 2 x 4 and on the right by one of dimensions 4 x 2.

2.5. **Multiplication in the reflectors.** In this section the case of multiplication in the reflectors is considered. If $k = 0$ in the characteristic equation (2.3.2) there results the foregoing situation in which there are two positive values of μ^2. If $0 < k < 1$ the μ^2's are still positive and the matrix Y_ν is as before. If $k = 1$, there is one positive μ^2 and one zero μ^2. The matrix Y_α takes the form

$$Y_\alpha =$$

$$\begin{pmatrix}
1 & x & e^{(\kappa_1^2 + \kappa_2^2)x} & e^{-(\kappa_1^2 + \kappa_2^2)x} \\
\dfrac{\lambda_1 \kappa_1^2}{\lambda_2 \kappa_2^2} & \dfrac{\lambda_1 \kappa_1^2 x}{\lambda_2 \kappa_2^2} & re^{(\kappa_1^2 + \kappa_2^2)x} & re^{-(\kappa_1^2 + \kappa_2^2)x} \\
0 & \lambda_1 x & se^{(\kappa_1^2 + \kappa_2^2)x} & -se^{-(\kappa_1^2 + \kappa_2^2)x} \\
0 & \dfrac{\lambda_1 \kappa_1^2 x}{\kappa_2^2} & -se^{(\kappa_1^2 + \kappa_2^2)x} & se^{-(\kappa_1^2 + \kappa_2^2)x}
\end{pmatrix}$$

or

$$Y_{\varkappa} =$$

$$
\begin{pmatrix}
x & \mathrm{sh}(\varkappa_1^2 + \varkappa_2^2)x & 1 & \mathrm{ch}(\varkappa_1^2 + \varkappa_2^2)x \\
\dfrac{\lambda_1 \varkappa_1^2 x}{\lambda_2 \varkappa_2^2} & r\,\mathrm{sh}(\varkappa_1^2 + \varkappa_2^2)x & \dfrac{\lambda_1 \varkappa_1^2}{\lambda_2 \varkappa_2^2} & r\,\mathrm{ch}(\varkappa_1^2 + \varkappa_2^2)x \\
\lambda_1 & s\,\mathrm{ch}(\varkappa_1^2 + \varkappa_2^2)x & 0 & s\,\mathrm{sh}(\varkappa_1^2 + \varkappa_2^2)x \\
\dfrac{\lambda_1 \varkappa_1^2}{\varkappa_2^2} & -s\,\mathrm{ch}(\varkappa_1^2 + \varkappa_2^2)x & 0 & -s\,\mathrm{sh}(\varkappa_1^2 + \varkappa_2^2)x
\end{pmatrix}
$$

where

$$
r = \frac{\lambda_1}{\lambda_2 \varkappa_2^2}\left[K_1^2 - (\varkappa_1^2 + \varkappa_2^2) \right] \quad ,
$$

$$
s = \lambda_1(\varkappa_1^2 + \varkappa_2^2) \quad .
$$

If $k > 1$, $Y_{\varkappa}(x)$ takes the form of $Y_0(x)$ as in (2.3.3).

3. **The multi-group, multi-reflector problem for the infinite slab pile.**

3.1. **The general formulation.** As in §2, let y, with an appropriate subscript to represent a particular group, represent the flux of the neutrons of this group in any of the $\nu + 1$ regions consisting of the pile and the reflector. The subscripts are chosen so as to increase with the mean energy of the group, that is, y_1 represents the flux of thermal neutrons, y_2 that of the slowest group of fast neutrons, and y_n that of the fastest group (the fission neutrons). The differential equations in any region have the form

$$\lambda_i \nabla^2 y_i - \lambda_i k_i^2 y_i + \lambda_{i+1} k_{i+1}^2 y_{i+1} = 0 \quad , \quad (i < n) \quad ,$$

(3.1.1)

$$\lambda_n \nabla^2 y_n + k \lambda_1 k_1^2 y_1 - \lambda_n k_n^2 y_n = 0 \quad ,$$

where the constant k is zero in a reflector without multiplication.

The boundary conditions prescribe the continuity of y_i and of $\lambda_i \nabla y_i$ at the intermediate boundaries and the vanishing of y_i at the outer boundary or boundaries.

3.2. The _infinite slab pile_. For the infinite slab pile the differential equations are especially simple in form since $\nabla^2 y_i$ becomes merely the second derivative with respect to x and all coefficients of the y_i and their derivatives are constant. It is convenient to introduce the additional variables

$$y_{n+j} = \lambda_j y_j' \quad , \qquad (j \le n) \quad ,$$

which makes it possible to replace the system of n second order equations by the 2n first order equations

$$y_j' = \lambda_j^{-1} y_{n+j} \quad , \qquad (j \le n) \quad ,$$

(3.2.1) $\quad y_{n+i}' = \lambda_i k_i^2 y_i - \lambda_{i+1} k_{i+1}^2 y_{i+1} \quad , \quad (i < n) \quad ,$

$$y_{2n}' = - k \lambda_1 k_1^2 y_1 + \lambda_n k_n^2 y_n \quad .$$

If the symbol y without a subscript denotes the column vector of components $y_1, y_2, \ldots, y_{2n}$, these equations can be written in the matrix form

$$(3.2.2) \qquad y' = My \quad,$$

where the 2n x 2n matrix M can be partitioned in the form

$$M = \begin{pmatrix} 0 & \Lambda^{-1} \\ M_1 & 0 \end{pmatrix} ,$$

with

$$\Lambda^{-1} = \begin{pmatrix} \lambda_1^{-1} & 0 & \cdots & 0 \\ 0 & \lambda_2^{-1} & \cdots & 0 \\ & & & \\ 0 & 0 & \cdots & \lambda_n^{-1} \end{pmatrix} ,$$

and

$$M_1 = \begin{pmatrix} \lambda_1 \kappa_1^2 & -\lambda_2 \kappa_2^2 & 0 & \cdots & 0 \\ 0 & \lambda_2 \kappa_2^2 & -\lambda_3 \kappa_3^2 & \cdots & 0 \\ & & & & \\ -\lambda_1 \kappa_1^2 & 0 & 0 & \cdots & \lambda_n \kappa_n^2 \end{pmatrix}$$

The characteristic equation

$$| M - \mu I | = 0$$

of the equation (3.2.2) is easily written down with the aid of the relation

$$\begin{pmatrix} -\mu I & \Lambda^{-1} \\ M_1 & -\mu I \end{pmatrix} \begin{pmatrix} I & 0 \\ \mu\Lambda & I \end{pmatrix} = \begin{pmatrix} 0 & \Lambda^{-1} \\ M_1 - \mu^2\Lambda & -\mu I \end{pmatrix} \quad ,$$

where the first matrix on the left is $M - \mu I$ and the second has the determinant unity. Hence

$$|M - \mu I| = |M_1 - \mu^2\Lambda||\Lambda^{-1}| = |M_1\Lambda^{-1} - \mu^2 I|$$

$$= \begin{vmatrix} \kappa_1^2 - \mu^2 & -\kappa_2^2 & 0 & \cdots & 0 \\ 0 & \kappa_2^2 - \mu^2 & -\kappa_3^2 & \cdots & 0 \\ \cdot & \cdot & \cdot & \cdot & \cdot \\ -k\,\kappa_1^2 & 0 & 0 & \cdots & \kappa_n^2 - \mu^2 \end{vmatrix}$$

The last determinant can be expanded immediately to yield the equation

$$(3.2.3) \quad (\kappa_1^2 - \mu^2)(\kappa_2^2 - \mu^2) \cdots (\kappa_n^2 - \mu^2) = k\,\kappa_1^2\kappa_2^2 \cdots \kappa_n^2 \quad .$$

It is clear that when $k = 0$ the roots of the characteristic equation are $\pm\kappa_i$. To investigate the case $k > 0$ consider the graph of the left member of (3.2.3) plotted against μ^2. This crosses the μ^2 - axis at κ_i^2 and crosses the vertical axis at $\kappa_1^2\kappa_2^2 \cdots \kappa_n^2$. The effect of subtracting $k\,\kappa_1^2\kappa_2^2 \cdots \kappa_n^2$

from the function is to raise the μ^2 - axis by this amount.
Hence, if $k < 1$ the real roots of the equation in μ^2 are all
positive; if $k = 0$ there is one zero root and all other real
roots are positive; if $k > 1$ there is one negative root and all
other real roots are positive. However, one cannot be assured
in general, for $n > 2$, that the roots in μ^2 are all real since,
for any $k > 0$, by making the difference between any pair of $\mathcal{K}$'s
sufficiently small one may introduce a pair of complex roots.

Whatever the nature of the characteristic roots, one can
always employ them to write down a set of $2n$ independent
solutions of the differential equations. If each of these
solutions is made a column of a $2n \times 2n$ matrix Y, as in $\S 2$,
then Y is a non-singular matrix satisfying the matrix
equation

$$ Y' = MY \quad . $$

From this point on the discussion for the case of two
groups given in $\S 2$ applies without significant changes for the
case of n groups. The equation for the determination of critical
pile size for all of the situations considered will involve a
determinant of order exactly n. The fundamental determinantal
equation may of course be used to find k if the pile and
reflector dimensions are fixed.

4. __The multi-group, multi-reflector problem for the
spherical pile.__

4.1. The differential equations and boundary
conditions. If the spherical pile has reflectors in the
form of spherical shells, such as to provide complete
spherical symmetry, then

$$r \nabla^2 y = \frac{d^2 (ry)}{dr^2} \quad .$$

Then the substitution

$$\left.\begin{aligned} v_1 &= r y_1 \quad , \\[2mm] v_{n+1} &= \lambda_1 v_1' \quad , \end{aligned}\right\} \qquad (1 \leq n) \quad ,$$

in the differential equations (3.1.1) yields 2n differential
equations in v_1, v_{n+1} of exactly the same form as those in
y_1, y_{n+1} for the slab pile. However, in the spherical case,
the boundary conditions which impose continuity upon y_1 and
$\lambda_1 y_1'$, when expressed in terms of v_1, require the continuity
of v_1 and

$$\lambda_1 \frac{d(v_1/r)}{dr} = \frac{v_{n+1}}{r} - \frac{\lambda_1 v_1}{r^2}$$

at the pile and reflector boundaries. Note in passing that
when the λ_1's are equal the v_{n+1}'s are also continuous and
the procedure is in all respects similar to the slab case.

4.2. Solution for the general case. The formation
of a fundamental set of solutions v constituting a non-singular

matrix V does not differ in any respect from the formation of such a matrix Y in the case of the slab pile. These solutions can be expressed as functions of r or of $\rho \cong r - r_{\varkappa - \varkappa}$, where $\varkappa$ designates the $\varkappa -$ th region, since any fundamental set expressed as functions of r remains a fundamental set when r is replaced throughout by ρ. In this procedure it must be noted that one may obtain solutions $y_i \cong v_i/r$ which become infinite under certain circumstances.

It is supposed now that in each region $\varkappa$ a matrix of solutions $V_\varkappa$ has been found and, for the sake of convenience, that this is so chosen that

$$V_{\varkappa} (r_{\varkappa -1}) \cong I, \quad (\varkappa \cong 1, 2, \ldots, \nu) \quad .$$

Since none of the $r_\varkappa$'s is known until the critical radius $r_0 \cong a$ is found, this choice involves expressing the solutions v as functions of $\rho \cong r - r_{\varkappa -1}$ and choosing $V_\varkappa$ to be the identity matrix when $\rho \cong 0$.

In the pile ($\varkappa \cong 0$) y must remain finite at $r \cong 0$, so that out of the $2n$ solutions n can be eliminated. Accordingly, the required solution is of the form

$$v_0 \cong V_{01} \, c_0 \quad ,$$

where c_0 is an $n -$ vector of constants and V_{01} is the $2n \times n$ matrix of v's (expressed in terms of trigonometric and hyperbolic

sines) whose first n rows vanish at $r = 0$. The rank of V_{01} must be n.

The continuity requirement involves the continuous vector

$$(4.2.1) \quad \begin{pmatrix} I & 0 \\ - r^{-2}\Lambda & r^{-1}I \end{pmatrix} V =$$

$$\begin{pmatrix} 1 & 0 & \cdots & 0 & 0 & 0 & \cdots & 0 \\ 0 & 1 & \cdots & 0 & 0 & 0 & \cdots & 0 \\ & & & & & & & \\ 0 & 0 & \cdots & 1 & 0 & 0 & \cdots & 0 \\ -\dfrac{\lambda_1}{r^2} & 0 & \cdots & 0 & \dfrac{1}{r} & 0 & \cdots & 0 \\ 0 & -\dfrac{\lambda_2}{r^2} & \cdots & 0 & 0 & \dfrac{1}{r} & \cdots & 0 \\ & & & & & & & \\ 0 & 0 & \cdots & -\dfrac{\lambda_n}{r^2} & 0 & 0 & \cdots & \dfrac{1}{r} \end{pmatrix} V$$

Thus, it is first of all required that

$$\begin{pmatrix} I & 0 \\ - a^{-2}\Lambda_0 & a^{-1}I \end{pmatrix} V_{01}(a)c_0 = \begin{pmatrix} I & 0 \\ - a^{-2}\Lambda_1 & a^{-1}I \end{pmatrix} c_1 \, .$$

provided the $V_1 = I$ at $r = r_0 = a$.

Note that

$$\begin{pmatrix} I & 0 \\ a^{-1}\Lambda_1 & a\,I \end{pmatrix} \begin{pmatrix} I & 0 \\ -a^{-2}\Lambda_1 & a^{-1}\,I \end{pmatrix} = \begin{pmatrix} I & 0 \\ 0 & I \end{pmatrix}.$$

so that (4.2.1) may be written as

$$\begin{pmatrix} I & 0 \\ a^{-1}\Lambda_1 & a\,I \end{pmatrix} \begin{pmatrix} I & 0 \\ -a^{-2}\Lambda_0 & a^{-1}\,I \end{pmatrix} V_{01}(a)c_0 = c_1 .$$

or

$$(4.2.2) \qquad \begin{pmatrix} I & 0 \\ a^{-1}(\Lambda_1 - \Lambda_0) & I \end{pmatrix} V_{01}(a)c_0 = c_1 .$$

Next, if the notation $t_\alpha = r_\alpha - r_{\alpha - 1}$ is introduced and if all v_α's are expressed as functions of $\rho = r - r_{\alpha - 1}$, the continuity requirement at the second boundary yields

$$\begin{pmatrix} I & 0 \\ -(a+t_1)^{-2}\Lambda_1 & (a+t_1)^{-1}I \end{pmatrix} V_1(t_1)c_1 = \begin{pmatrix} I & 0 \\ -(a+t_1)^{-2}\Lambda_2 & (a+t_1)^{-1}I \end{pmatrix} c_2 ,$$

or

$$(4.2.3) \begin{pmatrix} I & 0 \\ (a+t_1)^{-1}(\Lambda_2 - \Lambda_1) & I \end{pmatrix} V_1(t_1)c_1 = c_2 \quad .$$

Then from (4.2.2) and (4.2.3) it follows that

$$\begin{pmatrix} I & 0 \\ (a+t_1)^{-1}(\Lambda_2 - \Lambda_1) & I \end{pmatrix} V_1(t_1) \begin{pmatrix} I & 0 \\ a^{-1}(\Lambda_1 - \Lambda_0) & I \end{pmatrix} V_{01}(a)c_0 = c_2 \quad .$$

The next step gives

$$\begin{pmatrix} I & 0 \\ (a+t_1+t_2)^{-1}(\Lambda_3 - \Lambda_2) & I \end{pmatrix} V_2(t_2)c_2 = c_3 \quad .$$

which is used to eliminate c_2 in the last two equations. If this
procedure is continued one obtains finally

$$(4.2.4) \begin{pmatrix} I & 0 \\ \zeta_{j-1}^{-1}(\Lambda_j - \Lambda_{j-1}) & I \end{pmatrix} V_{j-1}(t_j) \cdots \begin{pmatrix} I & 0 \\ a^{-1}(\Lambda_1 - \Lambda_0) & I \end{pmatrix} V_{01}(a)c_0 = c_j$$

where $\quad \zeta_j = a + t_1 + t_2 + \cdots + t_j \quad .$

This matrix equation expresses the $2n$ components of c_j in
terms of the n components of c_0 and the unknown critical radius
$\underline{a}$. An additional matrix relation is needed for the elimination
of c_0, and this is found in the requirement that the solution
v_j shall vanish in its first n components at the outer boundary.

Now, $v_j = V_\nu c_\nu$, whence, if $V_{\nu 1}$ denotes the matrix of the

first n rows of V_ν , the condition in question takes the form

$$V_{\nu 1}(t_\nu)c_\nu = 0 \quad .$$

Accordingly, if the equation (4.2.4) is multiplied on the left

by $V_{\nu 1}$, there results the equation

$$V_{\nu 1}(t_\nu)\begin{pmatrix} I & 0 \\ \zeta_{\nu-1}^{-1}(\Lambda_\nu - \Lambda_{\nu-1}) & I \end{pmatrix} V_{\nu-1}(t_{\nu-1}) \cdots \begin{pmatrix} I & 0 \\ \zeta_0^{-1}(\Lambda_1 - \Lambda_0) & I \end{pmatrix} V_{01}(a)c_0 = 0 \quad .$$

The matrix coefficient of c_0 is n x n and its determinant must

vanish, that is,

$$\left| V_{\nu 1}(t_\nu) \cdots V_{01}(a) \right| = 0 \quad .$$

Note again that it has been presupposed that $V_\alpha(0) = I$. If

this normalization is not made the matrices $V_\alpha^{-1}(0)$ must also be

included in the matrix product. Note also that $\underline{a}$ does not occur

in any of the V_α's for $\alpha > 0$ but only in the elements of the

form $(a + t + \cdots + t_\alpha)^{-1}$ multiplied by a difference of Λ's in

consecutive regions. Note finally that $V_\alpha(t_\alpha)$ is of the same

form as in the slab case.

5. The multi-group, multi-reflector problem for the

infinite cylindrical pile.

5.1. The differential equations and boundary conditions.

If the cylindrical pile has reflectors in the form of cylindrical shells, such as to provide axial symmetry, then

$$\nabla^2 y = \frac{d^2 y}{dr^2} + \frac{1}{r}\frac{dy}{dr} \quad .$$

The differential equations in any region may be written in the form

$$\lambda_i \frac{d}{dr}\left(r\frac{dy_i}{dr}\right) = \lambda_i K_i^2\, r y_i + \lambda_{i+1} K_{i+1}^2\, r y_{i+1} = 0 \quad , \qquad (i < n),$$

$$\lambda_n \frac{d}{dr}\left(r\frac{dy_n}{dr}\right) + k \lambda_1 K_1^2\, r y_1 - \lambda_n K_n^2\, r y_n = 0 \quad .$$

The boundary conditions require the continuity of y_i and $\lambda_i \dfrac{dy_i}{dr}$ at the intermediate boundaries and the vanishing of y_i at the outer boundary or boundaries.

5.2. Solution for the general case.

The introduction of the variables

$$y_{n+j} = \lambda_j\, r y_j' \quad . \qquad (j \le n),$$

has the effect of replacing the system of n second order equations (5.1.1) by the 2n first order equations

$$y_i' = \lambda_i^{-1}\, r^{-1}\, y_{n+i} \quad . \qquad (i \le n),$$

$$(5.2.2) \quad y_{n+i}' = \lambda_i K_i^2\, r y_i - \lambda_{i+1} K_{i+1}^2\, r y_{i+1} \quad . \qquad (i < n),$$

$$y_{2n}' = -k\lambda_1 K_1^2\, r y_1 + \lambda_n K_n^2\, r y_n \quad .$$

If the symbol y without a subscript denotes the column vector of components y_1, y_2, ... , y_n, then the equations (5.2.2) can be written in the matrix form $y'' = My$, where M is the non-constant matrix of coefficients in the equations.

Solutions of the system (5.2.2) of the form

$$(5.2.3) \qquad y_i = a_i \, J_0(\mu r) \qquad . \qquad\qquad (i \leq n),$$

$$y_{n+i} = a_{n+i} \, r \, J_1(\mu r) \qquad .$$

are now sought. Substitution of (5.2.3) into (5.2.2) gives

$$- a_i \mu = \lambda_i^{-1} a_{n+i} \qquad . \qquad (i \leq n),$$

$$(5.2.4)$$

$$a_{n+i} \mu = \lambda_i \kappa_i^2 a_i - \lambda_{i+1} \kappa_{i+1}^2 a_{i+1} \qquad . \qquad (i < n),$$

$$a_{2n} \mu = - k \, \lambda_1 \kappa_1^2 a_1 + \lambda_n \kappa_n^2 a_n \qquad .$$

These equations have a non-trivial solution in a_i provided that

$$(5.2.5) \qquad \begin{vmatrix} -\mu I & \Lambda^{-1} \\[2ex] \eta_1 & -\mu I \end{vmatrix} = 0 \qquad .$$

where

$$\Lambda^{-1} = \begin{pmatrix} -\lambda_1^{-1} & 0 & \circ \circ \circ & 0 \\[2ex] 0 & -\lambda_2^{-1} & \circ \circ \circ & 0 \\[2ex] \circ & \circ & \circ & \circ \\[2ex] 0 & 0 & \circ \circ \circ & -\lambda_n^{-1} \end{pmatrix} \qquad .$$

and

$$E_1 = \begin{pmatrix} \lambda_1 \kappa_1^2 & -\lambda_2 \kappa_2^2 & 0 & \cdots & 0 \\ 0 & \lambda_2 \kappa_2^2 & -\lambda_3 \kappa_3^2 & \cdots & 0 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ -k\lambda_1 \kappa_1^2 & 0 & 0 & \cdots & \lambda_n \kappa_n^2 \end{pmatrix}$$

By a reduction similar to that used in § 3.2 the characteristic equation (5.2.5) becomes

(5.2.6) $(\kappa_1^2 + \mu^2)(\kappa_2^2 + \mu^2) \cdots (\kappa_n^2 + \mu^2) = k \kappa_1^2 \kappa_2^2 \cdots \kappa_n^2$

Note that the roots of this equation in μ^2 are the negatives of the roots of (3.2.2) in μ^2.

If J_0 and J_1 are replaced by Y_0 and Y_1 respectively in (5.2.3), the system (5.2.4), and consequently the equation (5.2.6), remains unchanged. However, if the combinations I_0, I_1 or K_0, K_1 are used the effect is the expected one of changing the signs of the roots of (5.2.6) in μ^2, or of replacing μ by $i\mu$.

If the roots of (5.2.6) in μ^2 are all real, then the functions J_0 and Y_0 correspond to the positive roots and the functions I_0 and K_0 to the negative roots. Thus, in this case at least, a set of $2n$ independent solutions of the differential equations can be found. As in the preceding sections, if each of these solutions is made a column of a $2n \times 2n$ matrix V, then V is a non-singular matrix satisfying the matrix equation

$$V^{0} = MV .$$

In the slab and spherical cases certain material simplifications were found by expressing the solutions in the α - th region as functions of a coordinate originating at the innermost boundary of the region. This simplification is not possible in the cylindrical case since the matrix M is no longer a constant matrix. Accordingly, the determination of critical pile size even in the simplest cases becomes an extremely arduous and uninviting task. The equation which yields the critical pile size may be written as the $n \times n$ determinantal equation

$$(5.2.7) \quad \left| V_{\nu 1}(\xi_\nu) V_\nu^{-1}(\xi_{\nu-1}) V_{\nu-1}(\xi_{\nu-1}) V_{\nu-1}^{-1}(\xi_{\nu-2}) \cdots V_{01}(a) \right| = 0 ,$$

where $\xi_\alpha = a + t_1 + t_2 + \cdots + t_\alpha$. V_{01} is a $2n \times n$ matrix of v^0s expressed in terms of the functions J_0 and I_0, which are finite

for $r \approx 0$, and where $V_{,)1}$ is an $n \times 2n$ matrix, the upper half of the matrix $V_{,)}$. Note that all of the matrices in (5.2.7) involve the pile size $\underline{a}$.

6. <u>Multi-group pile theory with continuously varying parameters in the reflector.</u>

6.1. <u>The case of the infinite slab pile.</u> In this discussion it is now assumed that the λ's and κ's of the multi-group pile theory equations are continuously varying parameters. In § 3 the system of n second order differential equations was replaced with a system of $2n$ first order equations with the aid of the substitution

$$ y_{n+j} = \lambda_j y''_j \quad . \qquad\qquad (j \leq n), $$

where the λ_j's are now functions of $\cdot$. It follows then from (3.2.1) that the system

$$ (\lambda_i y_i)'' - \lambda_i \kappa_i^2 y_i + \lambda_{i+1} \kappa_{i+1}^2 y_{i+1} = 0 \ . \ (i < n), $$

$$ (\lambda_n y_n)'' - \lambda_n \kappa_n^2 y_n + k \lambda_1 \kappa_1^2 y_1 = 0 \quad , $$

replaces the original system of n second order differential equations.

A convenient point of departure in this section is the consideration of the sequence of sets of equations

$$y_\alpha^0 = M_\alpha y_\alpha \quad ,$$

where y_α is the column vector of 2n components representing a solution of the equations in the α - th reflector, and M_α is a constant matrix composed of the parameters characteristic of that region. Heretofore no relation between the M's for distinct regions was assumed. The solutions y_α, however, were required in all cases to satisfy the continuity relations

$$y_\alpha (x_\alpha) = y_{\alpha+1}(x_\alpha) \quad .$$

If y is expressed in terms of the fundamental matrices Y then the continuity relations take the form

(6.1.1) $\qquad Y_\alpha (x_\alpha)c_\alpha = Y_{\alpha+1}(x_\alpha)c_{\alpha+1} \qquad .$

It is supposed now that the pile and reflectors constitute a single region with continuously varying parameters, or parameters having at most a finite number of discontinuities. Then the several sets of equations with constant coefficients are replaced by a single set of equations

$$Y^0 = M(x)y$$

with varying coefficients. Since the case in which M has components with discontinuities presents no essential complications, it will suffice to consider only the continuous

case. The interval from pile boundary to reflector boundary is broken up into slabs of thickness Δx and an approximation to the single set of equations with varying coefficients is achieved with a sequence of sets with constant coefficients. This sequence of sets has the same form as the one previously considered with

$$M_\alpha \equiv M(\xi_\alpha) , \qquad x_{\alpha-1} \le \xi_\alpha \le x_\alpha .$$

that is to say with M of the form taken by $M(x)$ when the components are evaluated at an arbitrary but fixed point within the α-th region.

The fundamental matrices Y_α are chosen as in § 2.4 so that

$$Y_\alpha(x_{\alpha-1}) \equiv I .$$

Then, from (5.1.1) it follows that

$$c_{\alpha+1} \equiv Y_\alpha(x_\alpha) c_\alpha .$$

The matrix $Y_\alpha(x_\alpha)$ may be expanded in powers of Δx to give

$$Y_\alpha(x_\alpha) \equiv Y_\alpha(x_{\alpha-1} + \Delta x)$$

$$\equiv Y_\alpha(x_{\alpha-1}) + Y_\alpha{}_\alpha \Delta x \qquad \ldots$$

$$\alpha_{\alpha-1} \cdots \eta_\alpha Y_\alpha(x_{\alpha-1}) \equiv M_\alpha I \equiv M_\alpha .$$

then

$$Y_\alpha(x_\alpha) \cong I + M_\alpha \Delta x + \ldots \quad .$$

It will suffice in this discussion to keep only the first two terms of this series.

By definition $y_\alpha(x) \cong Y_\alpha(x)c_\alpha$. Then it follows that $y_\alpha(x_{\alpha-1}) \cong Y_\alpha(x_{\alpha-1})c_\alpha \cong Ic_\alpha \cong c_\alpha$. Hence, if $y(x)$ represents the solution for the entire reflector, then $y(x)$ is identified with $y_1(x_0) \cong c_1$, where x_0 designates the inner boundary of the first reflector of the thickness Δx. Moreover, the entire approximation to the exact solution $y(x)$ evaluated at x_α is given by

$$y(x_\alpha) \sim c_{\alpha+1} \cong (I + M_\alpha \Delta x)c_\alpha$$

$$\cong (I + M_\alpha \Delta x)(I + M_{\alpha-1}\Delta x)c_{\alpha-1}$$

$$\cong \ldots$$

$$\cong (I + M_\alpha \Delta x)(I + M_{\alpha-1}\Delta x)\ldots(I + M_1 \Delta x)c \quad .$$

where $c \cong c_1$, or

$$y(x_\alpha) \sim \left[I + \sum_{\beta}^{1,\alpha} M_\beta \Delta x + \sum_{\beta > \beta'}^{1,\alpha} M_\beta M_{\beta'} \Delta_x^2 \right.$$
$$\left. + \sum_{\beta > \beta' > \beta''}^{1,\alpha} M_\beta M_{\beta'} M_{\beta''} \Delta_x^3 + \ldots \right] c \quad .$$

In the passage to the limit hold fixed the point x_α, but

allow the number of subdivisions to increase without limit
while Δx approaches zero. If the subscript α is suppressed
one obtains in the limit

$$y(x) = \left[I + \int_{x_0}^{x} M(\xi)d\xi + \int_{x_0}^{x} \int_{x_0}^{\xi} M(\xi)M(\xi')d\xi'd\xi \right.$$
$$\left. + \int_{x_0}^{x} \int_{x_0}^{\xi} \int_{x_0}^{\xi'} M(\xi)M(\xi')M(\xi'')d\xi''d\xi'd\xi + \cdots \right] c$$

If the matrix

$$(6.1.2) \quad K(x) = I + \int_{x_0}^{x} M(\xi)d\xi + \int_{x_0}^{x} \int_{x_0}^{\xi} M(\xi)M(\xi')d\xi'd\xi + \cdots$$

is introduced, the solution becomes

$$(6.1.3) \qquad y(x) = K(x)c \quad .$$

where $K(x)$ is a matrix whose columns constitute a fundamental
set of solutions and which reduces to the identity at x_0.

The solution $(6.1.3)$ can be obtained by a well-known
classical procedure. First of all it is noted that the original
equations

$$y' = M(x)y \quad , \qquad y(x_0) = c \quad .$$

are equivalent to the set of equations

$$y(x) = c + \int_{x_0}^{x} M(\xi)y(\xi)d\xi \quad .$$

Thus, by repeated substitutions, one finds that

$$y(x) = c + \int_{x_0}^{x} M(\xi)\left[c + \int_{x_0}^{\xi} M(\xi')y(\xi')d\xi'\right]d\xi$$

$$= \left[I + \int_{x_0}^{x} M(\xi)d\xi\right]c + \int_{x_0}^{x}\int_{x_0}^{\xi} M(\xi)M(\xi')y(\xi')d\xi'd\xi$$

$$= \ldots$$

This procedure gives rise once again to the matrix K. It is known that this series converges to the solution, for an arbitrary c, under very general conditions. The general matrix $K(x)$ of solutions, or the particular solution $y(x)$, could be approximated by computing a sufficient number of terms in the series (6.1.2). The repeated integrations may, however, become very laborious or totally impossible to carry out in closed form. Numerical integration involves the breaking up of the range of integration into subintervals and the introduction of interpolation polynomials. It may be simpler and less laborious to apply the slab procedure for obtaining the approximation. Since the slab procedure is no more complicated when the slabs are unequal in thickness, it should be especially advantageous when certain parameters vary at highly non-uniform rates, permitting greater thicknesses where the rates are all low, and requiring smaller subdivisions where some are high.

It is worthy of particular note that this whole procedure

is quite independent of the form of M and can be applied to any set whatsoever of linear equations.

In the problem of determining the critical size of a pile, assumed to have a uniform interior region within a reflector of continuously varying parameters, if T is the total thickness of the reflector the foregoing procedure yields a relation of the form

$$(6.1.3) \qquad y(a+T) \cong K(a+T)y(a) \qquad .$$

In this relation the $\underline{a}$ appears explicitly in $y(a) \cong c$, but not at all in either $y(a+T)$ or $K(a+T)$, the $a+T$ being merely a place label, that is, $y(a+T)$ and $K(a+T)$ in $(6.1.3)$ are functions of T alone. The $y(a+T)$ takes the place of $Y_{\jmath}(t_{\jmath})c_{\jmath}$ in $\S 2$. Moreover,

$$y(a) \cong Y_0(a)c_0 \cong Y_0(a)y(\cap) \qquad ,$$

if $Y_0(0) \cong I$. Accordingly, $(5.1.3)$ can be written in the form

$$y(a+T) \cong K(a+T)Y_0(a)y(0) \qquad .$$

where $\underline{a}$ occurs in Y_0 alone. The first n components of $y(a+T)$ are zero and the last n components of $y(0)$ are zero. Thus it follows that in the $2n \times 2n$ matrix $K(a+T)Y_0(a)$ the minor $n \times n$ matrix in the upper left-hand corner is singular. This is obtained by multiplying the upper half of K by the left hand

half of Y_0.

5.2. <u>The case of the spherical pile</u>. The discussion
in the preceding section applies almost without change to the
case of the spherical pile with a reflector with continuously
varying parameters. There is, however, a significant difference
in that the transformation employed above to obtain equations
with coefficients that are constant within each spherical
shell at the same time provides solutions which are discontinuous
in their last n components at the boundaries. The substitution
that provides continuity at the boundaries, viz, $y_{n+j} = \lambda_j y_j''$
yields a set of equations with coefficients which are functions
of r even within each uniform shell.

The advantage of having equations with constant coefficients
is, of course, that their solutions can be written down readily
in terms of exponentials, or trigonometric and hyperbolic sines
and cosines. However, once solutions are given in these terms
for the equations with constant coefficients (with discontinuities
in the solutions at the boundaries) a simple transformation
provides the corresponding solutions of the equations with
variable coefficients (with solutions that are continuous at
the boundaries). A further readjustment may be needed to
provide a matrix of solutions reducing to I at the inner boundary.
but this can always be effected. From this point, the procedure
is formally the same as for the slab case, and the spherical

shell approximation to the case of continuously varying parameters can be approximated by solving a finite number of sets of equations for uniform shells.

In conclusion it is noted that the form of the solution in the cylindrical case does not lend itself to the type of analysis used in the preceding sections for the problem of continuously varying parameters. At the present time then the cylindrical case with continuously varying parameters in the reflector constitutes an unsolved problem.